



SPECIFICATION:

CONTACT RATING: 6A 250VAC, 10A 125VAC

INSULATION RESISTANCE: 500V d.c. for 1 min.

ELECTRIC STRENGTH: 2000V a.c. for 1 min.

NO	DESCRIPTION	MATERIAL	QTY	SGS REPORT NO.
1	PIN	C3604 ALLOY COPPER, NICKEL	2	
2	HOUSING	ABS 777B	1	
3	GROUND	ABS 777B	1	
4	CONTACT	BRONZE, NICKEL	2	

Cd < 100ppm
 Cr+6 < 1000ppm
 Hg < 1000ppm
 Pb < 1,000ppm
 銅合金 Pb < 40,000ppm
 PBB < 1000ppm
 PBDE < 1000ppm

TOLERANCES
0.5MM-5MM=±0.2MM
5MM-30MM=±0.4MM
30MM-120MM=±0.6MM
120MM-315MM=±1.0MM
315MM-1000MM=±1.6MM
1000MM-2000MM=±2.4MM

NO	DESCRIPTION	DATE	DESIGNED BY	SCALE
95.7.28	UPDATE SGS報告	28 JUL 2006	C.J HUANG	1:1
94.2.22	增加規格說明		核准 Approved By	繪圖 Drew By
修正日期	修正說明		J.F. WANG	C.T WANG

大廣有限公司
DA KOANG CO., LTD.
 11330 EUROPE TYPE
 ADAPTOR PLUG, 6A 250V AC

REF. NO.