



Ordering Information

Part Number	Ampere	Voltage	Body Color
1526-2	2A	32 V	Lt.Gray 淡灰色
1526-3	3A	32 V	Violet 紫羅蘭色
1526-4	4A	32 V	Pink 粉紅
1526-5	5A	32 V	Tan 黃褐色
1526-7.5	7.5A	32 V	Brown 咖啡色
1526-10	10A	32 V	Red 紅色
1526-15	15A	32 V	Blue 藍色
1526-20	20A	32 V	Yellow 黃色
1526-25	25A	32 V	Natural 白色
1526-30	30A	32 V	Green 綠色



Specifications :

Rating	Blow Time
110%	4 Hours, Minimum
135%	0.75 to 1800 seconds
200%	0.15 to 5 seconds
350%	0.08 seconds, Maximum

Part No. : SUPER MINI series

*Fast Acting, Low Voltage For UP To 32V DC.

*Material : *Body : Plastic.

*Metal : Zinc Alloy Strip.

Material quality 材質	Plastic. 聚碳酸酯 Zinc Alloy 鋅合金
Unit 單位	mm
Error 誤差	± 0.2

大 廣 有 限 公 司 DAKOANG CO., LTD.

DATE	DWN	CHKD	APVD	MANAGFR
12.26.2011				

PART NAME: SUPER MINI FUSE

PART NUMBER: 1526

VERSION:4.0

TOLERANCE :±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT:mm



SCALE: